AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in this application.

LISTING OF CLAIMS:

1. (Currently Amended) A vehicular glazing panel comprising:

a pane of glass having opposite surfaces,

a first electrically conductive component which exists on [[a]] one of

the surfaces surface of the pane of glass which does not face another pane of glass

of the glazing panel, and

a second electrically conductive component which is joined to the first

component by a lead-free solder,

wherein the lead-free solder includes tin in an amount that is less than

50% by weight and a mechanical stress modifier, which inhibits the occurrence of a

stress fault in the pane of glass in the region of the solder, in the form of bismuth

metal or antimony metal.

2-3. (Canceled)

4. (Previously Presented) A glazing panel as claimed in claim 1 wherein

a fall in the stress (σ) generated in the pane of glass, after an initial rise, is described

as a function of time (t) by:

 $\sigma = A t^n$

wherein n is a measure of the creep rate of the lead-free solder and has a value less

than -0.130.

Attorney Docket No. <u>1021500-000138</u> Application No. 10/542,862

- 5. (Currently Amended) A glazing panel as claimed in claim 1 wherein the <u>one</u> surface of the pane of glass is provided around its periphery with a fired-ink band, on top of which the first electrically conductive component at least partially exists.
- 6. (Original) A glazing panel as claimed in claim 5 wherein the pane of glass is toughened and the stress fault therein manifests itself as blisters in the fired-ink band and in the corresponding regions of glass.
- 7. (Original) A glazing panel as claimed in claim 5 wherein the pane of glass is one ply of a laminate and the stress fault in the pane of glass manifests itself as one or more cracks therein.
- 8. (Previously Presented) A glazing panel as claimed in claim 1 wherein the stress fault in the glazing panel manifests itself as a structural defect in the interface between the solder and the first electrically conductive component.
- 9. (Previously Presented) A glazing panel as claimed in claim 1 wherein the first and second electrically conductive components comprise a busbar and an electrical connector respectively.
- 10. (Previously Presented) A glazing panel as claimed in claim 1 wherein the first and second electrically conductive components comprise an antenna element and an antenna connector respectively.

11. (Withdrawn) A method for joining together two or more electrically conductive components that are comprised in a vehicular glazing panel, which includes a pane of glass, the method comprising soldering the two or more electrically conductive components utilizing a lead-free solder that includes tin in an amount that is less than 50% by weight and a mechanical stress modifier, which inhibits the occurrence of a stress fault in the pane of glass in the region of the solder, in the form of bismuth metal and/or antimony metal.

12-19. (Canceled)

- 20. (Previously Presented) A glazing panel as claimed in claim 1 wherein the lead-free solder includes bismuth metal in an amount of 58% by weight as the mechanical stress modifier.
 - 21. (Canceled)
- 22. (New) A glazing panel as claimed in claim 1 wherein the first electrically conductive component is a printed layer of fired ink provided on the one surface of the pane of glass.